



EASY TO COLOR & PROTECT

Rubio® Monocoat color oils color and protect with just a single layer

The color oils are based on linseed oil and consist of 100% natural ingredients. They are free of water and solvents and contain 0% VOC. The Rubio® MONOCOAT Oil Plus is characterized by its exceptional water and heat resistance and creates an easy-care surface. Thanks to an innovative technology, the oil effectively bonds with the top cellulose fibers of the wood, creating an even, abrasion-resistant and overlap-free coloring. With just one application it colors and protects the wood and is also ideal as a renovation or care oil.

Over 40 color oils allow you to design the parquet floor according to personal preferences and individual furnishing style.

UNIQUE FEATURES

- The natural appearance of the wood is visibly highlighted
- The color oil is 100 percent natural and contains 0% VOC
- Neither water nor solvents are included
- High water and heat resistance ideal for installation in damp rooms
- 80% curing in just 2 days after application and fully resilient just 5 days after production

- Repairs and improvements are possible without overlaps or approaches
- No annual care necessary re-oiling and touchups only as needed
- Easy to Clean: 1 cleaner for all surfaces for daily maintenance cleaning and care











UNIVERSAL SOAP

Wood soap for regular cleaning all oiled wooden surfaces indoors

The Universal Soap is the ideal wood soap for cleaning oiled wooden floors. The product ensures optimal care of your parquet and at the same time thoroughly removes all traces of dirt and grease. The matt, natural appearance of the wood is retained. The universal soap is also very economical to use.



INSTRUCTIONS FOR USE:

- 1. Vacuum the surface. dust, sand, remove stones etc.
- **2.** A maximum of 50 to 100 ml of universal soap in a bucket with 10 liters of water.
- **3.** Clean the surface with a floor mop, mop clean with a mop or microfiber pad.
- **4.** Wipe the entire surface with clean water. Do not allow the water to act on the surface. It is sufficient to wipe the surface with a damp cloth.
- **5.** Let dry for about 15 minutes. Do not walk on the floor until it is completely dry.

SURFACE CARE

Ready-to-use spray version of Universal Soap

Surface Care is the practical and ready-touse version of Universal Soap. The environmentally friendly soap is suitable for cleaning small surfaces and for local stain removal on wooden floors, coffee tables, worktops, etc.



INSTRUCTIONS FOR USE:

- 1. Clean the surface. Remove dust, sand, stones etc.
- 2. Spray Surface Care onto the surface.
- 3. Wipe dry with a microfiber cloth.
- **4.** Allow the surface to dry for approximately 15 minutes. Do not re-enter the floor until it is completely dry.

SPECIAL STAIN REMOVERS

RMC Limespot Remover

Against alkaline contamination, such as: E.g. lime, rust, fertilizer, urine or heating water.



RMC Grease Remover

Against grease stains of all kinds, such as: E.g. floor wax residues, cooking oils, frying fat and streaks/residues from shoe soles.



RMC Tannin Remover

Against stains on wood containing tannic acid, such as: B. Water rings and stains from glasses, cans and flower pots, but also water damage and bleeding from wood ingredients can be removed.



INSTRUCTIONS FOR USE:

- 1. Spray stains with stain remover
- 2. Allow the product to take effect for a few minutes
- 3. Wipe up the solution and any remaining stains with a damp cloth
- **4.** If the stain is not completely removed, repeat the process until a satisfactory result is achieved
- 5. Allow the treated parquet surface to dry completely

After using RMC LIMESPOT REMOVER, RMC GREASE REMOVER and RMC TANNIN REMOVER, it may be necessary to re-treat the parquet floor with oil in the original color.



RMC Refresh Eco

Ready-to-use spray to refresh and renew the protective effect on oil-treated wooden surfaces

INSTRUCTIONS FOR USE:

- 1. Pre-treat the surface with RMC SOAP or RMC SURFACE CARE and allow to dry completely.
- 2. Spray the area with a small amount of RMC REFRESH ECO.
- 3. Use a microfiber cloth to wipe the product in the direction of the wood fibers.
- 4. Allow at least one hour for drying time.



RMC Oil Plus 2C

In the case of stubborn stains, severe wear and color loss, RMC OIL PLUS 2C refreshes the original color

INSTRUCTIONS FOR USE:

- 1. Sand the parquet surface with a floor polisher (120 V) or an RMCPAD GS320.
- 2. Thorough surface cleaning (vacuuming) and dust removal with RMC CLEANER.
- 3. Mix components A and B in a ratio of 3:1 and mix thoroughly for one to two minutes.
- **4.** Apply a small amount of RMC OIL PLUS 2C to the dry surface. and massage in gently with a sponge or RMC-PAD.

Tip: Work on small zones between 5-10 square meters one at a time.

- **5.** Allow to take effect for a short time. Within 15 minutes, remove excess oil with a dry cloth or white RMC-PAD. The surface must be semi-dry! All zones should be treated in this way.
- **6.** Waiting time for access/use: between 24 and 36 hours in well-ventilated rooms.



ATTENTION: Self-ignition of cloths containing RMC OIL PLUS 2C can occur. To avoid this, the cloths soaked with the product must be neutralized in water after use.

Colors for every taste and furnishing style Here you will find an overview of our color oils.

